

The LWW is an energy efficient wall wash fixture ideal for back lighting, up lighting and wall wash applications where dramatic lighting effects are desired. This unit uses high power LEDs that are available in warm white, pure white, red and blue. The housing is constructed of aluminum and is completely sealed for outdoor use.

Features

- Available in pure white, warm white, red and blue (supplied in 4' sections)
- Silver powder coat paint
- High power LEDs project light up to 65'
- Standard 5' 120V line cord with plug included
- Rated for indoor and outdoor use
- Controlled by DMX for ON/OFF dimming (DMX and programming furnished by other)
- Pre-installed 3-pin 1' signal cable for end to end connection
- Adjustable tilt design, up to 300° rotation for onsite adjustment
- 3 year warranty

Technical Specifications

- 3-pin signal connector
- Standard 120V power cord, single color, linear LED product
- Voltage: 100VAC-240VAC
- Frequency: 60Hz
- Weight: 13.48 lbs
- IP rating: IP65
- Dimensions: 47.25" long, 2.18" wide, 5" high (including mounting feet)
- Operating distance: Up to 30 units can be controlled with one DMX address
- Meets UL standards

Product Specifications

- LED specs:
- 50,000 hour rated life
- 36 LEDs mounted per 4' section
- Construction:
- 4' linear product
- Extruded aluminum housing, clear tempered glass
- Silver powder coat paint
- Fully sealed and gasketed unit for outdoor use
- Each unit has a five (5) foot grounded line cord
- Integrated driver
- Optic: 25° beam angle, 65' light projection
- Installation: Mounting brackets allow for the user to adjust the angle of the fixture based on project needs and allows for installation on various mounting surfaces
- Operating temperature: -4°F - 104°F (-20°C - 40°C)

Warranty

Any component that fails due to a manufacturing defect is guaranteed for three years. The warranty does not cover physical damage, abuse or instances of uncontrollable natural forces. See the full specialtyLED warranty document for detailed information. (Terms and conditions apply)

Model: _____ Date: _____
 Accessories: _____
 Job Name: _____ Type: _____



Applications

- Wall wash
- Flood light
- Bridge up lighting
- Stage/theater lighting
- Building parapet lighting



Ordering Information Example: LWW-WP-4-120V

Series	Color	Length	Voltage
LWW	WW ¹ = Warm White (3500K) WP ¹ = Pure White (5000K)	4 = 4 Feet	120V ² = 120VAC
	R = Red B = Blue	Notes	
		¹ Color temperatures can vary ±5%	
		² This is a 120VAC fixture - cutting off the cord plug will void warranty and UL Listing of the fixture	

Technical/Photometric Information (Data based on 120VAC application)

Color	Operating Current	Power Consumption	CCT	Lumens (lm/w)
Warm White	0.132A	15.84W	3500K	17.6 lm/w
Pure White	0.132A	15.84W	5000K	17.6 lm/w
Red	0.179A	21.48W	-	
Blue	0.179A	21.48W	-	

Accessories (Order As Separate Line Item)

Part Number	Image	Description
LWW-DATA-10		10' jumper cable with 3-pin DMX XLR.
LWW-POWER-10		10' power extension cable

Typical Accessories For LWW Single Color Installation

- LED Linear Wall Wash (LWW-WW-4-120V)
- Optional accessories (LWW-POWER-10)

Dimensions

